



公差带/General tolerances(mm)		公差带/General tolerances(mm)		公差带/General tolerances(mm)		公差带/General tolerances(mm)		公差带/General tolerances(mm)		公差带/General tolerances(mm)			
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	
~	~	~	~	~	~	~	~	~	~	~	~	~	
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.28	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50
											0.1/10	±2'	

ITEM	NAME OF PART	MATERIAL	NOTES
4	Nut	Steel	M3/Zn Plated
3	Housing2	PBT	UL94V-0
2	Pin	Copper	Sn Plated
1	Housing	PBT	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/30	300/30	300/70
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3		
额定电压/电涌/Rated Voltage(V)/Current(A)	/ / 400/32		
额定脉冲电压(KV)/Rate Impulse Voltage (KV)	/ / 4		
间距/Pitch(mm)/线数范围/Poles	7.62/N=02~12P		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON** 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

5EDGRM-7.62-XXP-1Y-00A(H)
 DRAWING NO.: 5EDGVM-7.62-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 1.5:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE

D
C
B
A

1 2 3 4 5 6